

**SPREAD SPECTRUM COMMUNICATION DEVICE
AND COMMUNICATION SYSTEM**

The present application is a continuation of
5 application Serial No. 09/558,373, filed April 26, 2000;
which is a continuation of application Serial No.
08/875,182, filed July 21, 1997, now U.S. Patent No.
6,134,264, the contents of which are incorporated herein
by reference.

10

BACKGROUND OF THE INVENTION

The present invention relates to surface acoustic
wave devices and communication devices.

In conventional spread spectrum communication
15 devices using the direct spreading method, a Barker code
was used as a pseudo noise code as described in 1985
ULTRASONICS SYMPOSIUM proceedings, pp. 145-148, for
example. It is known that this code does not depend on
the arrangement of an information code sequence and this
20 code has an auto-correlation side lobe of 1.

The Barker code has been found with the code length
of 13 or less. The Barker code has not been found with a
code length exceeding it. In the case where a processing
gain of a code length of at least 14 was required,
25 therefore, a code other than the Barker code, such as the
longest code sequence was used. In these code sequences,
however, a large side lobe rise is caused when the sign
of the information code is inverted. In general,
therefore, the error rate is increased.

30 An object of the present invention is to solve the
above described problem and provide a novel structure

of a spread spectrum communication device which uses a code sequence having a code length of at least 14, which does not depend on the arrangement of the information code, and which suppresses the side lobe rise of correlation signals.

5

SUMMARY OF THE INVENTION

The above described object can be achieved by employing a code sequence used by the present invention, i.e., a code shown in TABLES 1 through 9 as the pseudo noise code for spreading the power density spectrum of an input signal.

10

It has been confirmed by calculation conducted by the present inventors that the code shown in TABLES 1 through 9 has an auto-correlation coefficient side lobe of 3 or less. If this code is used, therefore, there is obtained a novel spread spectrum communication device and communication system which has a processing gain having an auto-correlation coefficient side lobe of at least 14, which does not depend on the arrangement of the information code, which suppresses the side lobe rise of the correlation signal, and which makes the error rate small. In addition, a surface acoustic wave device utilizing this characteristic is obtained.

15

The present invention relates to a novel code having a processing gain with a code length of at least 14 and an auto-correlation side lobe of 3 or less. The code length is determined in some cases by using harmon-

20

ics of the crystal (oscillation frequency in the case where a frequency multiplier is used). In other cases, the code length is generated independently of the clock frequency of the baseband digital circuit.

5 It is now assumed that the code length is determined by using harmonics of the crystal. If harmonics are generated by distorting the oscillation waveform of the clock frequency in order to make harmonic components large, for example, only odd-number components
10 included in harmonic components are typically generated. If its odd-number components are used as the clock of pseudo noise code generator, therefore, a value obtained by dividing the clock of the pseudo noise code generator by the clock frequency of the baseband digital circuit,
15 i.e., the code length is obtained. To be concrete, an odd-numbered code length such as 15, 17, 19, ... is obtained.

 In the case where the obtained odd-numbered code length is applied to a spread spectrum communication-
20 device, two code lengths are combined and used in some cases. To be concrete, it is a result of multiplication of odd-numbered code lengths. A value of at least 14 such as 15, 21, 25, 27, ... is used as the code length.

 In the case where the code length is generated
25 independently of the clock frequency of the baseband digital circuit, it doesn't matter at all whether the code length is even-numbered or odd-numbered and consequently values of at least 14, i.e., values 14, 15, 16,

17, ... are obtained.

In either case, a pseudo noise code formed by a large number of combinations in respective code lengths is present. Out of them, the present inventors found a
5 novel code which is 3 or less in auto-correlation side lobe and which is effective as the pseudo noise code used for spreading the power density spectrum of an input signal. The present inventors also found a novel pseudo noise generator capable of executing spreading (or
10 de-spreading) of the power density spectrum of an input signal by using those codes.

The following TABLES 1 through 9 show the pseudo noise code concerning the present invention.

TABLE 1 (n=14)

number	bj	max. corr. (forward)	max. corr. (back)	dc level
202	00000011001010	2	6	-6
332	00000101001100	2	6	-6
404	00000110010100	2	8	-6
405	00000110010101	2	6	-4
410	00000110011010	2	10	-4
470	00000111010110	2	10	-2
665	00001010011001	2	10	-4
691	00001010110011	2	10	-2
811	00001100101011	2	10	-2
821	00001100110101	2	10	-2
1883	00011101011011	2	10	2
2375	00100101000111	2	10	-2
2656	00101001100000	2	8	-6
2767	00101011001111	2	10	2
3232	00110010100000	2	6	-6
3247	00110010101111	2	10	2
3322	00110011111010	2	10	2

TABLE 1 (n=14, CONTINUED)

4021	00111110110101	2	10	4
4622	01001000001110	2	10	-4
5145	01010000011001	2	6	-4
5251	01010010000011	2	10	-4
5312	01010011000000	2	6	-6
5313	01010011000001	2	8	-4
5327	01010011001111	2	10	2
5535	01010110011111	2	6	4
5728	01011001100000	2	10	-4
5758	01011001111110	2	10	4
6092	01011111001100	2	10	2
6118	01011111100110	2	10	4
6575	01100110101111	2	10	4
6645	01100111110101	2	6	4
6650	01100111111010	2	10	4
6880	01101011100000	2	10	-2
7186	01110000010010	2	10	-4
7989	011111100110101	2	8	4
8090	011111110011010	2	10	4

TABLE 1 (n=14, CONTINUED)

8293	10000001100101	2	10	-4
8394	10000011001010	2	8	-4
9197	10001111101101	2	10	4
9503	10010100011111	2	10	2
9733	10011000000101	2	10	-4
9738	10011000001010	2	6	-4
9808	10011001010000	2	10	-4
10265	10100000011001	2	10	-4
10291	10100000110011	2	10	-2
10625	10100110000001	2	10	-4
10655	10100110011111	2	10	4
10848	10101001100000	2	6	-4
11056	10101100110000	2	10	-2
11070	10101100111110	2	8	4
11071	10101100111111	2	6	6
11132	10101101111100	2	10	4
11238	10101111100110	2	6	4
11761	10110111110001	2	10	4
12362	11000001001010	2	10	-4

TABLE 1 (n=14, CONTINUED)

13061	11001100000101	2	10	-2
13136	11001101010000	2	10	-2
13151	11001101011111	2	6	6
13616	11010100110000	2	10	-2
13727	11010110011111	2	8	6
14008	11011010111000	2	10	2
14500	11100010100100	2	10	-2
15562	11110011001010	2	10	2
15572	11110011010100	2	10	2
15692	111101010001100	2	10	2
15718	11110101100110	2	10	4
15913	11111000101001	2	10	2
15973	11111001100101	2	10	4
15978	11111001101010	2	6	4
15979	11111001101011	2	8	6
16051	11111010110011	2	6	6
16181	11111100110101	2	6	6

TABLE 2 (n=15)

number	bj	max. corr. (forward)	max. corr. (back)	dc level
202	000000011001010	3	7	-7
332	000000101001100	3	7	-7
345	000000101011001	3	7	-5
394	000000110001010	3	7	-7
404	000000110010100	3	9	-7
405	000000110010101	3	7	-5
410	000000110011010	3	11	-5
618	000001001101010	3	7	-5
652	000001010001100	3	11	-7
664	000001010011000	3	11	-7
665	000001010011001	3	11	-5
678	000001010100110	3	7	-5
691	000001010110011	3	7	-3
710	000001011000110	3	11	-5
718	000001011001110	3	7	-3
808	000001100101000	3	11	-7
809	000001100101001	3	11	-5

TABLE 2 (n=15, CONTINUED)

810	000001100101010	3	7	-5
811	000001100101011	3	9	-3
821	000001100110101	3	7	-3
922	000001110011010	3	11	-3
1140	000010001110100	3	11	-5
1221	000010011000101	3	11	-5
1299	000010100010011	3	11	-5
1305	000010100011001	3	11	-5
1356	000010101001100	3	11	-5
1380	000010101100100	3	11	-5
1610	000011001001010	3	11	-5
1620	000011001010100	3	11	-5
1642	000011001101010	3	11	-3
1672	000011010001000	3	11	-7
2152	000100001101000	3	11	-7
2224	000100010110000	3	11	-7
2228	000100010110100	3	11	-5
2281	000100011101001	3	11	-3
2579	000101000010011	3	11	-5

TABLE 2 (n=15, CONTINUED)

2587	0001010000011011	3	11	-3
2656	000101001100000	3	11	-7
2824	0001011000001000	3	11	-7
3232	000110010100000	3	11	-7
3748	000111010100100	3	9	-3
3821	000111011101101	3	9	3
4188	001000001011100	3	11	-5
4305	001000011010001	3	11	-5
4419	001000101000011	3	11	-5
4449	001000101100001	3	11	-5
4792	001001010111000	3	9	-3
4874	0010011000001010	3	7	-5
4944	001001101010000	3	11	-5
5079	001001111010111	3	11	3
5139	001010000010011	3	11	-5
5145	001010000011001	3	11	-5
5312	001010011000000	3	9	-7
5313	001010011000001	3	11	-5
5424	001010100110000	3	11	-5

TABLE 2 (n=15, CONTINUED)

5535	001010110011111	3	9	3
5619	001010111110011	3	11	3
5649	001011000010001	3	11	-5
5768	001011010001000	3	11	-5
5904	001011100010000	3	11	-5
6154	001100000001010	3	7	-7
6165	001100000010101	3	7	-5
6187	001100000010101	3	11	-3
6304	001100010100000	3	11	-7
6405	001100100000101	3	11	-5
6464	001100101000000	3	7	-7
6465	001100101000001	3	11	-5
6480	001100101010000	3	11	-5
6495	001100101011111	3	7	3
6645	001100111110101	3	11	3
6922	001101100001010	3	11	-3
7087	001101110101111	3	11	5
7127	001101111010111	3	11	5
7147	001101111101011	3	11	5

TABLE 2 (n=15, CONTINUED)

7428	001110100000100	3	11	-5
7867	001111010111011	3	11	5
7901	001111011011101	3	11	5
7989	001111100110101	3	11	3
8369	010000010110001	3	11	-5
8377	010000010111001	3	11	-3
8394	010000011001010	3	11	-5
8610	010000110100010	3	11	-5
8730	010001000011010	3	11	-5
8734	010001000011110	3	11	-3
8771	010001001000011	3	11	-5
8898	010001011000010	3	11	-5
9230	010010000001110	3	9	-5
9287	010010001000111	3	9	-3
9738	010011000001010	3	11	-5
10252	010100000001100	3	7	-7
10265	010100000011001	3	7	-5
10278	010100000100110	3	11	-5
10290	010100000110010	3	11	-5

TABLE 2 (n=15, CONTINUED)

10291	010100000110011	3	11	-3
10340	010100001100100	3	7	-5
10348	010100001101100	3	11	-3
10432	010100011000000	3	7	-7
10544	010100100110000	3	11	-5
10624	010100110000000	3	7	-7
10625	010100110000001	3	7	-7
10626	010100110000010	3	11	-5
10627	010100110000011	3	11	-3
10655	010100110011111	3	7	3
10848	010101001100000	3	7	-5
11040	010101100100000	3	7	-5
11056	010101100110000	3	11	-3
11070	010101100111110	3	9	3
11071	010101100111111	3	7	5
11238	010101111100110	3	7	3
11251	010101111110011	3	7	5
11298	010110000100010	3	11	-5
11456	010110011000000	3	11	-5

TABLE 2 (n=15, CONTINUED)

11488	010110011100000	3	11	-3
11518	010110011111110	3	11	5
11887	010111001101111	3	11	5
11998	010111011011110	3	11	5
12211	010111110110011	3	11	5
12217	010111110111001	3	11	5
12238	010111111001110	3	11	5
12262	010111111100110	3	11	5
12549	011000100000101	3	11	-5
12609	011000101000001	3	11	-5
12669	011000101111101	3	11	3
12704	011000110100000	3	11	-5
12810	011001000001010	3	11	-5
12929	011001010000001	3	11	-5
12960	011001010100000	3	7	-5
12991	011001010111111	3	7	5
13151	011001101011111	3	11	5
13231	011001110101111	3	11	5
13290	011001111101010	3	7	3

TABLE 2 (n=15, CONTINUED)

13291	011001111101011	3	11	5
13301	01100111110101	3	7	5
13306	01100111111010	3	11	5
13329	011010000010001	3	11	-5
13431	011010001110111	3	11	3
13727	011010110011111	3	11	5
14254	011011110101110	3	11	5
14354	011100000010010	3	9	-5
14717	011100101111101	3	11	5
14752	011100110100000	3	7	-3
14842	011100111111010	3	11	5
14971	011101001111011	3	11	5
15094	011101011110110	3	11	5
15307	011101111001011	3	11	5
15337	011101111101001	3	11	5
15394	011110000100010	3	11	-3
15547	011110010111011	3	11	5
15802	011110110111010	3	11	5
15978	011111001101010	3	9	3

TABLE 2 (n=15, CONTINUED)

15979	0111111001101011	3	11	5
16051	0111111010110011	3	11	5
16057	0111111010111001	3	11	5
16181	0111111100110101	3	9	5
16217	0111111101011001	3	11	5
16282	011111110011010	3	11	5
16485	100000001100101	3	11	-5
16550	100000010100110	3	11	-5
16586	100000011001010	3	9	-5
16710	100000101000110	3	11	-5
16716	100000101001100	3	11	-5
16788	100000110010100	3	11	-5
16789	100000110010101	3	9	-3
16965	100001001000101	3	11	-5
17220	10001101000100	3	11	-5
17373	100001111011101	3	11	3
17430	100010000010110	3	11	-5
17460	100010000110100	3	11	-5
17673	100010100001001	3	11	-5

TABLE 2 (n=15, CONTINUED)

17796	100010110000100	3	11	-5
17925	100011000000101	3	11	-5
18015	100011001011111	3	7	3
18050	100011010000010	3	11	-5
18413	100011111101101	3	9	5
18513	100100001010001	3	11	-5
19040	100101001100000	3	11	-5
19336	100101110001000	3	11	-3
19438	100101111101110	3	11	5
19461	100110000000101	3	11	-5
19466	1001100000001010	3	7	-5
19476	1001100000010100	3	11	-5
19477	1001100000010101	3	7	-3
19536	100110001010000	3	11	-5
19616	100110010100000	3	11	-5
19776	100110101000000	3	7	-5
19807	100110101011111	3	7	5
19838	100110010111110	3	11	5
19957	100110111110101	3	11	5

TABLE 2 (n=15, CONTINUED)

20063	100111001011111	3	11	5
20098	100111010000010	3	11	-3
20158	100111010111110	3	11	5
20218	100111011111010	3	11	5
20505	101000000000101	3	11	-5
20529	101000000110001	3	11	-5
20550	101000001000110	3	11	-5
20556	101000001001100	3	11	-5
20769	101000100100001	3	11	-5
20880	101000110010000	3	11	-5
21249	101001100000001	3	11	-5
21279	101001100011111	3	11	3
21311	101001100111111	3	11	5
21469	101001111011101	3	11	5
21516	101010000001100	3	7	-5
21529	101010000011001	3	7	-3
21696	101010011000000	3	7	-5
21697	101010011000001	3	9	-3
21711	101010011001111	3	11	3

TABLE 2 (n=15, CONTINUED)

21727	101010011011111	3	7	5
21919	101010110011111	3	7	5
22112	101011001100000	3	7	-3
22140	101011001111100	3	11	3
22141	101011001111101	3	11	5
22142	101011001111110	3	9	5
22143	101011001111111	3	7	7
22223	101011011001111	3	11	5
22335	101011100111111	3	7	7
22419	101011110010011	3	11	3
22427	101011110011011	3	7	5
22476	101011111001100	3	11	3
22477	101011111001101	3	11	5
22489	101011111011001	3	11	5
22502	10101111110110	3	7	5
22515	101011111110011	3	7	7
23029	101100111110101	3	11	5
23480	101101110111000	3	9	3
23537	101101111110001	3	9	5

TABLE 2 (n=15, CONTINUED)

23869	101110100111101	3	11	5
23996	101110110111100	3	11	5
24033	101110111100001	3	11	3
24037	101110111100101	3	11	5
24157	101111001011101	3	11	5
24373	101111100110101	3	11	5
24390	101111101000110	3	11	3
24398	101111101001110	3	11	5
24778	110000011001010	3	11	-3
24866	110000100100010	3	11	-5
24900	110000101000100	3	11	-5
25339	110001011111011	3	11	5
25620	110010000010100	3	11	-5
25640	110010000101000	3	11	-5
25680	110010001010000	3	11	-5
25845	110010011110101	3	11	3
26122	110011000001010	3	11	-3
26272	110011010100000	3	7	-3
26287	110011010101111	3	11	5

TABLE 2 (n=15, CONTINUED)

26302	110011010111110	3	11	5
26303	110011010111111	3	7	7
26362	110011011111010	3	11	5
26463	110011101011111	3	11	7
26580	110011111010100	3	11	3
26602	110011111101010	3	7	5
26613	110011111110101	3	7	7
26863	110100011101111	3	11	5
26999	110100101110111	3	11	5
27118	110100111101110	3	11	5
27148	110101000001100	3	11	-3
27232	110101001100000	3	9	-3
27343	110101011001111	3	11	5
27454	110101100111110	3	11	5
27455	110101100111111	3	9	7
27622	110101111100110	3	11	5
27628	110101111101100	3	11	5
27688	110110000101000	3	11	-3
27823	110110010101111	3	11	5
27893	110110011110101	3	7	5

TABLE 2 (n=15, CONTINUED)

27975	110110101000111	3	9	3
28318	110111010011110	3	11	5
28348	110111010111100	3	11	5
28462	110111100101110	3	11	5
28579	110111110100011	3	11	5
28946	111000100010010	3	9	-3
29019	111000101011011	3	9	3
29535	111001101011111	3	11	7
29943	111010011110111	3	11	7
30111	111010110011111	3	11	7
30180	111010111100100	3	11	3
30188	111010111101100	3	11	5
30486	111011100010110	3	11	3
30539	111011101001011	3	11	5
30543	111011101001111	3	11	7
30615	111011110010111	3	11	7
31095	111100101110111	3	11	7
31125	111100110010101	3	11	3
31147	111100110101011	3	11	5

TABLE 2 (n=15, CONTINUED)

31157	111100110110101	3	11	5
31387	111101010011011	3	11	5
31411	111101010110011	3	11	5
31462	111101011100110	3	11	5
31468	111101011101100	3	11	5
31546	111101100111010	3	11	5
31627	111101110001011	3	11	5
31845	111110001100101	3	11	3
31946	111110011001010	3	7	3
31956	111110011010100	3	9	3
31957	111110011010101	3	7	5
31958	111110011010110	3	11	5
31959	111110011010111	3	11	7
32049	111110100110001	3	7	3
32057	111110100111001	3	11	5
32076	111110101001100	3	7	3
32089	111110101011001	3	7	5
32102	111110101100110	3	11	5
32103	111110101100111	3	11	7

TABLE 2 (n=15, CONTINUED)

32115	111110101110011	3	11	7
32149	111110110010101	3	7	5
32357	111111001100101	3	11	5
32362	111111001101010	3	7	5
32363	111111001101011	3	9	7
32373	111111001110101	3	7	7
32422	111111010100110	3	7	5
32435	111111010110011	3	7	7
32565	111111100110101	3	7	7

TABLE 3 (n=17)

number	bj	max. corr. (forward)	max. corr. (back)	dc level
2931	00000101101110011	3	9	-1
3253	00000110010110101	3	9	-3
3286	00000110011010110	3	9	-3
3685	00000111001100101	3	13	-3
3693	00000111001101101	3	11	-1
3893	00000111100110101	3	9	-1
3929	00000111101011001	3	11	-1
5555	00001010110110011	3	9	-1
5838	00001011011001110	3	11	-1
6443	00001100100101011	3	9	-3
6581	00001100110110101	3	13	-1
6775	00001101001110111	3	13	1
6877	00001101011011101	3	9	1
7386	00001110011011010	3	11	-1
7642	00001110111011010	3	9	1
7859	00001111010110011	3	9	1

TABLE 3 (n=17, CONTINUED)

7901	00001111011011101	3	11	3
7917	00001111011101101	3	13	3
9039	00010001101001111	3	13	-1
9125	00010001110100101	3	11	-3
9171	00010001111010011	3	9	-1
9189	00010001111100101	3	9	-1
11111	00010101101100111	3	9	1
12121	00010111101011001	3	9	1
12887	00011001001010111	3	9	-1
14773	00011100110110101	3	11	1
15269	00011101110100101	3	13	1
15284	00011101110110100	3	9	1
15716	00011110101100100	3	11	-1
15718	00011110101100110	3	9	1
16217	0001111101011001	3	9	3
17596	00100010010111100	3	13	-3
18110	00100011010111110	3	9	1
19499	00100110000101011	3	13	-3

TABLE 3 (n=17, CONTINUED)

19578	00100110001111010	3	11	-1
19832	00100110101111000	3	11	-1
20590	00101000001101110	3	9	-3
20716	00101000011101100	3	13	-3
21054	00101001000111110	3	13	-1
21310	00101001100111110	3	9	1
22223	00101011011001111	3	9	3
22427	00101011110011011	3	13	3
23075	00101101000100011	3	13	-3
23480	00101101110111000	3	9	1
24749	00110000010101101	3	9	-3
24757	00110000010110101	3	11	-3
24765	00110000010111101	3	9	-1
25183	00110001001011111	3	9	1
25775	00110010010101111	3	9	1
25871	00110010100001111	3	9	-1
26578	00110011111010010	3	9	1
26743	00110100001110111	3	9	1
28180	00110111000010100	3	13	-3

TABLE 3 (n=17, CONTINUED)

30539	00111011101001011	3	13	3
31300	00111101001000100	3	13	-3
31946	00111110011001010	3	9	1
31958	00111110011010110	3	13	3
33229	01000000111001101	3	9	-3
34291	01000010111110011	3	9	1
35087	01000100100001111	3	11	-3
35151	01000100101001111	3	9	-1
35193	01000100101111001	3	9	-1
35301	01000100111100101	3	13	-1
37135	01001000100001111	3	13	-3
37150	01001000100011110	3	9	-3
37663	01001001100011111	3	11	1
38387	01001010111110011	3	9	3
38860	01001011111001100	3	9	1
38862	01001011111001110	3	11	3
39165	01001100011111101	3	9	3
41433	01010000111011001	3	9	-1
42183	01010010011000111	3	11	-1
42191	01010010011001111	3	13	1

TABLE 3 (n=17, CONTINUED)

42399	01010010110011111	3	9	3
42483	01010010111110011	3	11	3
42527	01010011000011111	3	9	1
42620	01010011001111100	3	9	1
45175	01011000001110111	3	9	1
45277	01011000011011101	3	13	1
45855	01011001100011111	3	13	3
45953	01011001110000001	3	9	-3
46105	01011010000011001	3	9	-3
46151	010110100001000111	3	13	-1
46199	01011010001110111	3	11	3
46704	01011011001110000	3	11	-1
46960	01011011101110000	3	9	1
48228	01011110001100100	3	11	-1
48921	01011111000011001	3	9	3
49885	01100001011011101	3	9	1
50366	01100010010111110	3	13	1
51445	01100100011110101	3	9	1
51719	01100101000000111	3	9	-3

TABLE 3 (n=17, CONTINUED)

51735	01100101000010111	3	9	-1
51743	01100101000011111	3	11	1
52600	01100110101111000	3	9	1
52741	01100111000000101	3	9	-3
53157	0110011110100101	3	9	3
53486	01101000011101110	3	13	1
54880	01101011001100000	3	9	-3
54908	01101011001111100	3	13	3
56801	01101110111100001	3	13	3
59009	01110011010000001	3	13	-3
59088	01110011011010000	3	11	-1
59346	01110011111010010	3	11	3
60436	01110110000010100	3	9	-3
60950	01110111000010110	3	13	1
61577	01111000010001001	3	13	-3
61714	01111000100010010	3	9	-3
63636	01111100010010100	3	13	-1
63892	01111100110010100	3	9	1
64070	01111101001000110	3	13	1

TABLE 3 (n=17, CONTINUED)

64196	011111110001100101	3	9	1
64613	011111110001100101	3	9	3
64817	011111110100110001	3	13	3
66254	10000001011001110	3	13	-3
66458	10000001110011010	3	9	-3
66875	10000010100111011	3	9	-1
67001	10000010110111001	3	13	-1
67179	10000011001101011	3	9	-1
67435	10000011101101011	3	13	1
69357	10000111011101101	3	9	3
69494	10000111101110110	3	13	3
70121	10001000111101001	3	13	-1
70635	10001001111101011	3	9	3
71725	10001100000101101	3	11	-3
71983	10001100100101111	3	11	1
72062	10001100101111110	3	13	3
74270	10010001000011110	3	13	-3
76163	10010100110000011	3	13	-3
76191	10010100110011111	3	9	3

TABLE 3 (n=17, CONTINUED)

77585	10010111100010001	3	13	-1
77914	100110000001011010	3	9	-3
78330	10011000111111010	3	9	3
78471	10011001010000111	3	9	-1
79328	10011010111100000	3	11	-1
79336	10011010111101000	3	9	1
79352	10011010111111000	3	9	3
79626	10011011100001010	3	9	-1
80705	10011101101000001	3	13	-1
81186	10011110100100010	3	9	-1
82150	10100000011100110	3	9	-3
82843	10100001110011011	3	11	1
84111	10100100010001111	3	9	-1
84367	10100100110001111	3	11	1
84872	10100101110001000	3	11	-3
84920	10100101110111000	3	13	1
84966	10100101111100110	3	9	3
85118	10100110001111110	3	9	3
85216	10100110011100000	3	13	-3

TABLE 3 (n=17, CONTINUED)

85794	10100111100100010	3	13	-1
85896	10100111110001000	3	9	-1
88451	10101100110000011	3	9	-1
88544	10101100111100000	3	9	-1
88588	10101101000001100	3	11	-3
88672	10101101001100000	3	9	-3
88880	10101101100110000	3	13	-1
88888	10101101100111000	3	11	1
89638	10101111000100110	3	9	1
91906	10110011100000010	3	9	-3
92209	10110100000110001	3	11	-3
92211	10110100000110011	3	9	-1
92684	10110101000001100	3	9	-3
93408	10110110011100000	3	11	-1
93921	10110111011100001	3	9	3
93936	10110111011110000	3	13	3
95770	10111011000011010	3	13	1
95878	10111011010000110	3	9	1
95920	10111011010110000	3	9	1

TABLE 3 (n=17, CONTINUED)

95984	10111011011110000	3	11	3
96780	10111101000001100	3	9	-1
97842	10111111000110010	3	9	3
99113	11000001100101001	3	13	-3
99125	11000001100110101	3	9	-1
99771	11000010110111011	3	13	3
100532	11000100010110100	3	13	-3
102891	11001000111101011	3	13	3
104328	11001011110001000	3	9	-1
104493	11001100000101101	3	9	-1
105200	11001101011110000	3	9	1
105296	11001101101010000	3	9	-1
105888	11001110110100000	3	9	-1
106306	11001111101000010	3	9	1
106314	11001111101001010	3	11	3
106322	11001111101010010	3	9	3
107591	11010010001000111	3	9	-1
107996	11010010111011100	3	13	3
108644	11010100001100100	3	13	-3

TABLE 3 (n=17, CONTINUED)

108848	11010100100110000	3	9	-3
109761	11010110011000001	3	9	-1
110017	11010110111000001	3	13	1
110355	11010111100010011	3	13	3
110481	11010111110010001	3	9	3
111239	11011001010000111	3	11	1
111493	11011001110000101	3	11	1
111572	11011001111010100	3	13	3
112961	11011100101000001	3	9	-1
113475	11011101101000011	3	13	3
114854	11100000010100110	3	9	-3
115353	11100001010011001	3	9	-1
115355	11100001010011011	3	11	1
115787	11100010001001011	3	9	-1
115802	11100010001011010	3	13	-1
116298	11100011001001010	3	11	-1
118184	11100110110101000	3	9	1
118950	11101000010100110	3	9	-1
119960	11101010010011000	3	9	-1

TABLE 3 (n=17, CONTINUED)

121882	11101110000011010	3	9	1
121900	111011100000101100	3	9	1
121946	111011100001011010	3	11	3
122032	11101110010110000	3	13	1
123154	11110000100010010	3	13	-3
123170	11110000100100010	3	11	-3
123212	11110000101001100	3	9	-1
123429	11110001000100101	3	9	-1
123685	11110001100100101	3	11	1
124194	11110010100100010	3	9	-1
124296	11110010110001000	3	13	-1
124490	11110011001001010	3	13	1
124628	11110011011010100	3	9	3
125233	11110100100110001	3	11	1
125516	11110101001001100	3	9	1
127142	111110000010100110	3	11	1
127178	111110000011001010	3	9	1
127378	11111000110010010	3	11	1
127386	11111000110011010	3	13	3

TABLE 3 (n=17, CONTINUED)

127785	11111001100101001	3	9	3
127818	11111001101001010	3	9	3
128140	11111010010001100	3	9	1

TABLE 4 (n=19)

number	bj	max. corr. (forward)	max. corr. (back)	dc level
3241	0000000110010101001	3	15	-7
10342	0000010100001100110	3	15	-7
26897	0000110100100010001	3	15	-7
28946	0000111000100010010	3	7	-7
33705	0001000001110101001	3	11	-5
34996	0001000100010110100	3	11	-7
37560	0001001001010111000	3	15	-5
59976	0001110101001001000	3	15	-5
61146	0001110111011011010	3	7	3
64429	0001111101110101101	3	9	5
66385	0010000001101010001	3	11	-7
70117	0010001000111100101	3	15	-3
74076	0010010000101011100	3	15	-5
86785	0010101001100000001	3	15	-7
92296	0010110100010001000	3	11	-7
95265	0010111010000100001	3	11	-5

TABLE 4 (n=19, CONTINUED)

97651	0010111110101110011	3	15	5
100875	0011000101000001011	3	15	-5
104970	0011001101000001010	3	15	-5
119844	0011101010000100100	3	15	-5
129885	0011111101101011101	3	11	7
130261	0011111110011010101	3	15	5
139806	01000100010000011110	3	11	-5
141571	0100010100100000011	3	11	-7
145426	0100011100000010010	3	15	-7
147682	0100100000011100010	3	15	-7
148592	0100100010001110000	3	7	-7
151815	0100101000100000111	3	9	-5
164556	0101000001011001100	3	15	-5
173571	0101010011000000011	3	15	-5
181179	0101100001110111011	3	15	3
187320	0101101101110111000	3	7	3
204961	0110010000010100001	3	15	-7
209056	0110011000010100000	3	15	-7
217591	0110101000111110111	3	11	5

TABLE 4 (n=19, CONTINUED)

218751	0110101011001111111	3	15	7
229006	011011111010001110	3	15	5
232438	011100010111110110	3	15	5
240123	011101010011111011	3	11	7
244559	011101110110100111	3	15	7
246306	0111100001000100010	3	11	-5
251865	0111101011111011001	3	15	7
253579	0111101111010001011	3	11	5
260523	0111111100110101011	3	15	7
263764	1000000011001010100	3	15	-7
270708	1000010000101110100	3	11	-5
272422	1000010100000100110	3	15	-7
277981	1000011110111011101	3	11	5
279728	1000100010010110000	3	15	-7
284164	1000101011000000100	3	11	-7
291849	1000111010000001001	3	15	-5
295281	1001000000101110001	3	15	-5
305536	1001010100110000000	3	15	-7
306696	10010101110000001000	3	11	-5

TABLE 4 (n=19, CONTINUED)

315231	1001100111101011111	3	15	7
319326	1001101111101011110	3	15	7
336967	1010010010001000111	3	7	-3
343108	1010011110001000100	3	15	-3
350716	1010101100111111100	3	15	5
359731	10101111101000110011	3	15	5
372472	10110101110111111000	3	9	5
375695	10110111011100001111	3	7	7
376605	10110111111000011101	3	15	7
378861	10111000011111101101	3	15	7
382716	10111010110111111100	3	11	7
384481	10111011110111100001	3	11	5
394026	1100000001100101010	3	15	-5
394402	11000000010010100010	3	11	-7
404443	1100010101111011011	3	15	5
419317	1100110010111110101	3	15	5
423412	1100111010111110100	3	15	5
426636	11010000010100001100	3	15	-5
429022	1101000101111011110	3	11	5

TABLE 4 (n=19, CONTINUED)

431991	1101001011101110111	3	11	7
437502	1101010110011111110	3	15	7
450211	1101101111010100011	3	15	5
454170	1101110111000011010	3	15	3
457902	1101111110010101110	3	11	7
459858	1110000010001010010	3	9	-5
463141	1110001000100100101	3	7	-3
464311	1110001010110110111	3	15	5
486727	1110110110101000111	3	15	5
489291	1110111011101001011	3	11	7
490582	1110111110001010110	3	11	5
495341	1111000111011101101	3	7	7
497390	1111001011011101110	3	15	7
513945	1111101011110011001	3	15	7
521046	1111111001101010110	3	15	7

TABLE 5 (n=21)

number	bj	max. corr. (forward)	max. corr. (backward)	dc level
14773	000000011100110110101	3	15	-3
23865	0000001011101000111001	3	13	-3
29546	000000111001101101010	3	11	-3
31157	000000111100110110101	3	11	-1
47731	0000010111010001110011	3	15	-1
55754	000001101100111001010	3	11	-3
59029	000001110011010010101	3	11	-3
59093	000001110011011010101	3	15	-1
59245	000001110011101101101	3	15	1
60249	000001110101101011001	3	15	-1
62294	000001111001101010110	3	17	-1
81210	000010011110100111010	3	15	-1
89708	000010101111001101100	3	21	-1
183260	000101100101111011100	3	17	1
231861	000111000100110110101	3	15	-1
248388	000111100101001000100	3	13	-5
255570	000111110011001010010	3	13	-1
257750	000111110111011010110	3	13	5

TABLE 5 (n=21, CONTINUED)

276270	001000011011100101110	3	11	-1
281208	001000100101001111000	3	13	-5
281571	001000100101111100011	3	13	-1
331699	001010000111110110011	3	15	1
336446	001010010001000111110	3	13	-3
397237	001100000111110110101	3	15	1
406623	001100011010001011111	3	15	1
410091	001100100000111101011	3	15	-1
442901	001101100001000010101	3	13	-5
446288	001101100111101010000	3	21	-1
459446	001110000001010110110	3	11	-3
460219	001110000010110111011	3	13	1
490088	001110111101001101000	3	17	1
509010	001111100010001010010	3	13	-3
521034	001111111001101001010	3	17	3
521046	001111111001101010110	3	17	5
549238	010000110000101110110	3	17	-3
598815	010010010001100011111	3	15	-1
607356	010010100010001111100	3	13	-3

TABLE 5 (n=21, CONTINUED)

609528	010010100110011111000	3	13	-1
614638	010010110000011101110	3	13	-1
659673	010100001000011011001	3	15	-5
672243	010100100000111110011	3	15	-1
674879	010100100110000111111	3	11	1
674943	010100100110001111111	3	15	3
675271	010100100110111000111	3	15	1
678396	010100101100111111100	3	17	3
684896	010100111001101100000	3	11	-3
693023	010101001001100011111	3	15	1
709407	010101101001100011111	3	11	3
711104	010101101100111000000	3	11	-3
718739	0101011110111110010011	3	13	5
759696	010111001011110010000	3	15	-1
783558	010111111010011000110	3	21	3
812538	011000110010111111010	3	21	3
813247	011000110100010111111	3	13	3
827125	011001001111011110101	3	15	5
828703	011001010010100011111	3	15	1

TABLE 5 (n=21, CONTINUED)

846657	011001110101101000001	3	15	-1
874976	011010101100111100000	3	17	-1
875004	011010101100111111100	3	17	5
880376	011010110111011111000	3	13	5
895004	011011010100000011100	3	11	-3
896785	011011010111100010001	3	13	1
905410	011011101000011000010	3	17	-3
957828	011101001110110000100	3	11	-1
975058	011101110000011010010	3	13	-1
975177	011101110000101001001	3	13	-1
1018004	011111000100010010100	3	13	-3
1025305	011111010010100011001	3	15	1
1071846	100000101101011100110	3	15	-1
1079147	100000111011101101011	3	13	3
1121974	100010001111010110110	3	13	1
1122093	100010001111100101101	3	13	1
1139323	100010110001001111011	3	11	1
1191741	100100010111100111101	3	17	3
1200366	100100101000011101110	3	13	-1

TABLE 5 (n=21, CONTINUED)

1202147	100100101011111100011	3	11	3
1216775	100101001000100000111	3	13	-5
1222147	100101010011000000011	3	17	-5
1222175	100101010011000011111	3	17	1
1250494	100110001010010111110	3	15	1
1268448	100110101101011100000	3	15	-1
1270026	100110110000100001010	3	15	-5
1283904	1001110010111101000000	3	13	-3
1284613	100111001101000000101	3	21	-3
1313593	101000000101100111001	3	21	-3
1337455	101000110100001101111	3	15	1
1378412	101010000100001101100	3	13	-5
1386047	101010010011000111111	3	11	3
1387744	101010010110011100000	3	11	-3
1404128	101010110110011100000	3	15	-1
1412255	101011000110010011111	3	11	3
1418755	101011010011000000011	3	17	-3
1421880	101011011001000111000	3	15	-1
1422208	101011011001110000000	3	15	-3

TABLE 5 (n=21, CONTINUED)

1422272	101011011001111000000	3	11	-1
1424908	101011011111000001100	3	15	1
1437478	101011110111100100110	3	15	5
1482513	101101001111100010001	3	13	1
1487623	101101011001100000111	3	13	1
1489795	101101011101110000011	3	13	3
1498336	101101101110011100000	3	15	1
1547913	101111001111010001001	3	17	3
1576105	110000000110010101001	3	17	-5
1576117	110000000110010110101	3	17	3
1588141	110000011101110101101	3	13	3
1607063	110001000010110010111	3	17	-1
1636932	110001111101001000100	3	13	-1
1637705	110001111110101001001	3	11	3
1650863	110010011000010101111	3	21	1
1654250	110010011110111101010	3	13	5
1687060	110011011111000010100	3	15	1
1690528	110011100101110100000	3	15	-1
1699914	1100111111000001001010	3	15	-1

TABLE 5 (n=21, CONTINUED)

1760705	110101101110111000001	3	13	3
1765452	110101111000001001100	3	15	-1
1815580	110111011010000011100	3	13	1
1815943	110111011010110000111	3	13	5
1820881	110111100100011010001	3	11	1
1839401	111000001000100101001	3	13	-5
1841581	111000001100110101101	3	13	1
1848763	111000011010110111011	3	13	5
1865290	111000111011001001010	3	15	1
1913891	111010011010000100011	3	17	-1
2007443	111101010000110010011	3	21	1
2015941	111101100001011000101	3	15	1
2034857	111110000110010101001	3	17	1
2036902	111110001010010100110	3	15	1
2037906	111110001100010010010	3	15	-1
2038058	111110001100100101010	3	15	1
2038122	111110001100101101010	3	11	3
2041397	111110010011000110101	3	11	3
2049420	111110100010110001100	3	15	1

TABLE 5 (n=21, CONTINUED)

2065994	111111000011001001010	3	11	1
2067605	111111000110010010101	3	11	3
2073286	111111010001011000110	3	13	3
2082378	111111100011001001010	3	15	3

TABLE 6 (n=23)

number	bj	max. corr. (forward)	max. corr. (backward)	dc level
29362	00000000111001010110010	3	15	-7
75541	00000010010011100010101	3	11	-7
86422	00000010101000110010110	3	15	-7
115861	00000011100010010010101	3	11	-7
271825	00001000010010111010001	3	11	-7
272197	00001000010011101000101	3	15	-7
333508	00001010001011011000100	3	11	-7
345892	00001010100011100100100	3	15	-7
463141	00001110001000100100101	3	11	-7
476197	00001110100010000100101	3	11	-7
496708	00001111001010001000100	3	15	-7
543651	00010000100101110100011	3	11	-5
789930	00011000000110110101010	3	15	-5
1031085	0001111011101110101101	3	11	7
1082833	00100001000010111010001	3	11	-7
1083205	00100001000011101000101	3	11	-7
1116052	00100010000011110010100	3	11	-7
1119472	00100010001010011110000	3	15	-7

TABLE 6 (n=23, CONTINUED)

1142932	00100010111000010010100	3	11	-7
1160272	00100011011010001010000	3	11	-7
1181041	0010010000001010110001	3	15	-7
1208656	00100100111000101010000	3	15	-7
1345348	00101001000011101000100	3	11	-7
1372228	00101001111000001000100	3	11	-7
1524769	00101110100010000100001	3	11	-7
1906423	00111010001011011110111	3	11	5
1994730	00111100110111111101010	3	15	7
2285833	01000101110000100001001	3	11	-7
2429191	01001010001000100000111	3	11	-7
2533120	01001101010011100000000	3	15	-7
2807832	01010101101100000011000	3	15	-5
2846271	01010110110111000111111	3	11	7
2854335	01010111000110110111111	3	11	7
2882364	01010111111101100111100	3	15	7
2965230	01011010011111011101110	3	15	7
2997135	01011011011101110001111	3	11	7
3010191	01011011110111010001111	3	11	7

TABLE 6 (n=23, CONTINUED)

3050991	01011101000110111101111	3	15	7
3051387	01011101000111101111011	3	11	7
3128430	01011111011110001101110	3	11	7
3141006	01011111110110110001110	3	15	7
3458368	01101001100010101000000	3	15	-7
3652701	01101111011110001011101	3	11	7
3715035	01110001010111111011011	3	15	7
3726330	01110001101101111111010	3	15	7
3812847	01110100010110111110111	3	11	7
3813243	01110100010111101111011	3	11	7
3874554	01110110001111011111010	3	11	7
3910974	01110111010110100111110	3	11	7
3915354	01110111011111001011010	3	15	7
3922494	01110111101101000111110	3	11	7
4058763	01111011110111010001011	3	11	7
4074990	01111100010110111101110	3	11	7
4086510	01111100101101011101110	3	11	7
4302097	10000011010010100010001	3	11	-7
4313617	10000011101001000010001	3	11	-7

TABLE 6 (n=23, CONTINUED)

4329844	10000100001000101110100	3	11	-7
4466113	10001000010010111000001	3	11	-7
4473253	10001000100000110100101	3	15	-7
4477633	10001000101001011000001	3	11	-7
4514053	10001001110000100000101	3	11	-7
4575364	1000101110100001000010	3	11	-7
4575760	10001011101001000010000	3	11	-7
4662277	10001110010010000000101	3	15	-7
4673572	10001110101000000100100	3	15	-7
4735906	10010000100001110100010	3	11	-7
4930239	10010110011101010111111	3	15	7
5247601	10100000001001001110001	3	15	-7
5260177	10100000100001110010001	3	11	-7
5337220	10100010111000010000100	3	11	-7
5337616	10100010111001000010000	3	15	-7
5378416	10100100001000101110000	3	11	-7
5391472	10100100100010001110000	3	11	-7
5423377	10100101100000100010001	3	15	-7
5506243	10101000000010011000011	3	15	-7

TABLE 6 (n=23, CONTINUED)

5534272	1010100011100100100000	3	11	-7
5542336	1010100100100011100000	3	11	-7
5580775	10101010010011111100111	3	15	5
5855487	10110010101100011111111	3	15	7
5959416	10110101110111011111000	3	11	7
6102774	10111010001111011110110	3	11	7
6393877	11000011001000000010101	3	15	-7
6482184	11000101110100100001000	3	11	-5
6863838	11010001011101111011110	3	11	7
7016379	110101100001111101111011	3	11	7
7043259	11010110111100010111011	3	11	7
7179951	11011011000111010101111	3	15	7
7207566	11011011111101010001110	3	15	7
7228335	11011100100101110101111	3	11	7
7245675	11011101000111101101011	3	11	7
7269135	11011101110101100001111	3	15	7
7272555	11011101111100001101011	3	11	7
7305402	11011110111100010111010	3	11	7
7305774	11011110111101000101110	3	11	7

TABLE 6 (n=23, CONTINUED)

7357522	11100000100010001010010	3	11	-7
7598677	1110011111001001010101	3	15	5
7844956	11101111011010001011100	3	11	5
7891899	11110000110101110111011	3	15	7
7912410	11110001011101111011010	3	11	7
7925466	11110001110111011011010	3	11	7
8042715	11110101011100011011011	3	15	7
8055099	11110101110100100111011	3	11	7
8116410	11110111101100010111010	3	15	7
8116782	11110111101101000101110	3	11	7
8272746	11111100011101101101010	3	11	7
8302185	11111101010111001101001	3	15	7
8313066	11111101101100011101010	3	11	7
8359245	1111111000110101001101	3	15	7

TABLE 7 (n=25)

number	bj	max. corr. (forward)	max. corr. (backward)	dc level
381638	0000001011101001011000110	3	11	-5
446005	0000001101100111000110101	3	13	-3
465770	0000001110001101101101010	3	13	-3
473782	0000001110011101010110101	3	13	-1
897941	0000011011011001110010101	3	13	-1
947565	0000011100111010101101101	3	15	1
2054758	000011111010110100110010	3	13	1
2054886	0000111110101101011100110	3	11	3
3275446	0001100011111010101101010	3	17	3
3672501	0001110000000100110110101	3	15	-5
3672793	0001110000000101011011001	3	13	-5
4808590	0010010010101111110001110	3	15	1
4945678	0010010110111011100001110	3	13	1
6550893	001100011111010101101101	3	13	5
6561626	0011001000001111010110101	3	11	-1
6692698	0011001100001111010110101	3	13	1
7093738	0011011000011110111101010	3	11	3
7345002	0011100000001001101101010	3	13	-5

TABLE 7 (n=25, CONTINUED)

7345586	0011100000001010101101010	3	17	-5
9609331	0100100101010000001110011	3	13	-5
9610015	0100100101010001100011111	3	15	-1
10178588	010011011010100000011100	3	17	-5
10805191	0101001001101111111000111	3	15	5
10950975	0101001110001100100111111	3	13	3
11297951	0101011000110010010011111	3	13	1
11374620	0101011011001000000011100	3	13	-5
11383232	0101011011011000111000000	3	13	-3
11499628	01010111101111100001101100	3	11	3
11923532	0101101011111000001001100	3	11	-1
11923660	01011010111110000011001100	3	13	1
13014848	0110001101001011101000000	3	11	-5
13197255	0110010010101111111000111	3	13	5
13415920	0110011001011010111110000	3	13	1
13546992	0110011101011010111110000	3	11	3
14334400	01101101010111100111000000	3	13	-1
14335768	0110110101011111100011000	3	17	3
14802340	01110000111011110110100100	3	13	1

TABLE 7 (n=25, CONTINUED)

14939428	011100011111010100100100	3	15	1
18615003	1000111000000101011011011	3	15	-1
18752091	1000111100010001001011011	3	13	-1
19218663	1001001010100000011100111	3	17	-3
19220031	1001001010100011000111111	3	13	1
20007439	1001100010100101000001111	3	11	-3
2013851	1001100110100101000001111	3	13	-1
20357176	100110110101000000111000	3	13	-5
20539583	1001110010110100010111111	3	11	5
21630771	1010010100000111100110011	3	13	-1
21630899	1010010100000111110110011	3	11	1
22054803	1010100001000011110010011	3	11	-3
22171199	1010100100100111000111111	3	13	3
22179811	1010100100110111111100011	3	13	5
22256480	1010100111001101101100000	3	13	-1
22603456	1010110001110011011000000	3	13	-3
22749240	1010110110010000000111000	3	15	-5
23375843	1011001001010111111100011	3	17	5
23944416	1011011010101110011100000	3	15	1

TABLE 7 (n=25, CONTINUED)

23945100	10110110101011111110001100	3	13	5
26208845	110001111110101001001101	3	17	5
26209429	110001111110110010010101	3	13	5
26460693	1100100111100001000010101	3	11	-3
26861733	1100110011110000010100101	3	13	-1
26992805	1100110111110000010100101	3	11	1
27003538	1100111000000101010010010	3	13	-5
28608753	11011010010001000111110001	3	13	-1
28745841	1101101101010000001110001	3	15	-1
29881638	111000111111101010100100110	3	13	5
29881930	111000111111101100100101010	3	15	5
30278985	11100111000000010101001001	3	17	-3
31499545	1111000001010010100011001	3	11	-3
31499673	1111000001010010110011001	3	13	-1
32606866	1111100011000101010010010	3	15	-1
32656490	111110010010011000110101010	3	13	1
33080649	11111100011000010101001001	3	13	1
33088661	111111000111001001001010101	3	13	3
33108426	1111110010011000011100101010	3	13	3
33172793	1111110100010110100111001	3	11	5

TABLE 8 (n=27)

number	bj	max. corr. (forward)	max. corr. (backward)	dc level
930410	000000011100011001001101010	3	15	-7
1624362	000000110001100100100101010	3	15	-9
1860757	000000111000110010010010101	3	15	-7
15798573	000111100010001000100101101	3	11	-5
39566215	010010110111011101110000111	3	11	5
44341440	010101001001001100011000000	3	15	-9
45245312	010101100100110001110000000	3	15	-7
45534783	010101101101100111000111111	3	15	7

TABLE 9 (n=29)

number	b _j	max. corr. (forward)	max. corr. (backward)	dc level
11687143	00000101100100101010011100111	3	15	-3
20815162	00001001111011001110100111010	3	15	1
29650650	00001110001000110111011011010	3	17	-1
52082271	0001100011010101011001011111	3	15	3
52401586	0001100011111100101011011010	3	15	1
52417970	0001100001111101010110110010	3	11	3
69590574	00100001001011101111000101110	3	13	1
70752046	00100001101111001011100101110	3	19	1
79132430	001001011011101110111100001110	3	15	3
162536693	01001101100000001110011110101	3	15	-1
162873112	01001101101010011111100011000	3	15	1
162889496	01001101101010111111100011000	3	11	3
169410125	01010000110001111111001001101	3	15	1
191808624	01011011011101100010001110000	3	17	-1
194459536	010111001011100110111110010000	3	15	1
236838308	011100001110111011110110100100	3	15	3
244282500	01110100011110111010010000100	3	19	-1
245185924	01110100111010011110110000100	3	19	1

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a system block diagram of a spread spectrum communication device showing a first application example of the present invention; FIG. 2 is a diagram illustrating a signal code sequence; FIG. 3 is a system block diagram of a part of a communication device showing a second application example of the present invention; FIG. 4 shows a surface acoustic wave device using a second application example of the present invention; FIG. 5 is a system block diagram of a spread spectrum communication device showing a third application example of the present invention; FIG. 6 shows a code sequence used in the third application example of the present invention; FIG. 7 shows a matched signal used in the third application example of the present invention; FIG. 8 shows the frequency response of a matched filter used in the third application example of the present invention; FIG. 9 shows a conventional Barker code (13 chips); FIG. 10 shows a matched signal in the case where the conventional Barker code (13 chips) is used; FIG. 11 shows the frequency response of a matched filter in the case where the conventional Barker code (13 chips) is used; FIG. 12 shows tap coefficients of a matched filter using a fourth application example of the present invention; FIG. 13 shows a matched signal used in the fourth application example of the present invention; FIG. 14 shows tap coefficients of a matched filter using a fifth application example of the present invention; FIG. 15 shows a

matched signal used in the fifth application example of the present invention; FIG. 16 is a system block diagram of a spread spectrum communication device showing a sixth application example of the present invention; FIG. 17 is a system block diagram of a part of a communication device showing a seventh application example of the present invention; FIG. 18 is a system block diagram of a part of a communication device showing an eighth application example of the present invention; FIG. 19 is a system block diagram of a part of a communication device showing a ninth application example of the present invention; FIG. 20 is a system block diagram of a part of a communication device showing a tenth application example of the present invention; FIG. 21 is a system block diagram of a part of a communication device showing an eleventh application example of the present invention; and FIG. 22 shows a communication system using a device shown in a twelfth application example of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Hereafter, modes for carrying out the present invention will be described by referring to FIGS. 1 through 23.

However, some modes hereafter described are shown in order to explain application examples for carrying out the present invention. Modes for carrying out the present invention are never limited to application

examples described here.

FIG. 1 is a diagram schematically showing a spread spectrum communication device to which the present invention has been applied. An information signal is inputted from an input terminal 1, multiplied in a mixer 2 by a signal supplied from a pseudo noise code generator 3, furthermore multiplied in a mixer 4 by a carrier supplied from an oscillator 5, amplified in an amplifier 6, and outputted from an antenna 7. Here, a code shown in TABLES 1 through 9 was used as the pseudo noise code.

In a receiving system, a signal inputted from the antenna 7 is amplified in an amplifier 8, demodulated, converted to a digital signal in a square wave output circuit 9, and taken out from an output terminal 10 as an information signal. Here, a code similar to the above described code was used as a reference code for demodulating the information. (It coincides with the pseudo noise code of the transmitter.) FIG. 2 is a diagram showing a signal code sequence. In the case of the synchronous detection system, a signal code sequence S_k corresponds to 1 and 0 of the information code, and it is represented as

$$S_k = \begin{cases} m_{\text{mod}(k/n)}(\text{data}=1\text{or}0) \\ -m_{\text{mod}(k/n)}(\text{data}=0\text{or}1) \end{cases} \quad (\text{Expression 1})$$

where m_j ($j = 1, 2, \dots, n$; $n = \text{code length}$) corresponds to a pseudo noise code b_j shown in TABLES 1 through 9, and it is represented by the following equation.

$$m_j = \begin{cases} 1(b_j = 1) \\ -1(b_j = 0) \end{cases} \quad (\text{Expression 2})$$

In the same way, in the case of the delay detection system, the signal code sequence S_k is represented by the following equation.

$$S_k = \begin{cases} m_{\text{mod}(k/n)} S_{k-1} (\text{data} = 1 \text{ or } 0) \\ -m_{\text{mod}(k/n)} S_{k-1} (\text{data} = 0 \text{ or } 1) \end{cases} \quad (\text{Expression 3})$$

Denoting a reference code of the receiving side by M_j , a correlation coefficient O_k is represented by the following equation.

$$O_k = \sum_{j=1}^n S_{k+j-1} M_j \quad (\text{Expression 4})$$

10 In the case where $M_j = m_j$, the correlation coefficient O_k represents an auto-correlation coefficient and it is represented by the following equation.

$$O_k = \sum_{j=1}^n S_{k+j-1} m_j \quad (\text{Expression 5})$$

Sub-peaks other than correlation peaks ($\text{mod}(k/n) = 1$) are referred to as side lobes. As this value becomes smaller, the error rate of the receiver is typically reduced. For the case where the code length is at least 14, such a code that the side lobe value calculated by using the Expression 5 is 3 or less is shown in TABLES 1 through 9. Calculation conducted here corresponds to all arrangements (0, 0), (0, 1), (1, 0) and (1, 1) of 0 and 1 of the information code. (The above described 0 and 1 of the information code indicate that they are mutually in the relation of inverted code.) Calculation was conducted as to such an arrangement of S_k that signs whereby m_j is multiplied are (+, +, -). That is, calculating to Expression 5 above is performed on a single code sequence S_k which includes M_{js} have signs (+, +, -), respectively (i.e., $S_k = +M_{j1} + M_{j2} - M_{j3}$). (In the remaining case where the signs are (-, -, +), a result equal in absolute value and opposite in sign to the above described result is obtained. In other words, only the polarity is different. Therefore, the above described calculation alone suffices.)

In TABLES 1 through 9, "bj" is a derived code sequence, and "number" is a value obtained by regarding the "bj" as a binary number and converting it to a decimal number. Furthermore, "max corr. (forward)" is a side lobe value, and "max corr. (backward)" is a maximum value of correlation value obtained in the case where codes are

reversed bilaterally. Furthermore, "dc level" is the sum total of n "mj"s. As a matter of course, similar results are obtained even if code inversion ($1 \Leftrightarrow 0$) is conducted on these codes. Since it takes an enormous time to
5 conduct calculations, inverted codes are omitted for lengthy code lengths. If these codes are used as the pseudo noise code, there is obtained a spread spectrum communication device having a processing gain of at least 14 in auto-correlation side lobe, having smaller
10 time-axis side lobes of received matched signal, having a smaller error rate, and having favorable characteristics.

A second application example of the present invention will now be described by referring to FIG. 3. The same components as those in FIG. 1 showing the first
15 application example are denoted by like numerals. FIG. 3 is a diagram showing a receiving part of the second application example of the present invention. A received signal taken in from an antenna 7 is amplified in an
amplifier 8, converted to a matched signal in a matched
20 filter 11, detected in a detector circuit 12, demodulated, converted to a digital signal by a square wave output circuit 13, and outputted from an output terminal 10. In the present application example, a matched filter is used as a demodulating element. This results in a feature
25 that the circuit can be simply formed.

A third application example of the present invention will now be described by referring to FIGS. 4 and 5.

FIG. 4 is a diagram schematically showing a SAW (surface acoustic wave) matched filter 18. On a SAW substrate 14, an input interdigital electrode set 15 and an output interdigital electrode set 16 are disposed.

5 Furthermore, in order to suppress a reflected wave coming from a substrate face, a sound absorbing material 17 is coated. The input interdigital electrode set 15 has such a structure that the electrode polarity is inverted every electrode. (The electric polarity differs depending upon
10 whether the electrode is connected to an upper common electrode or a lower common electrode.) The output interdigital electrode set 16 has a matched filter structure in which the electrode polarity is inverted in association with the pseudo noise code. As the substrate
15 14, an ST-cut crystal substrate is used in order to prevent the center frequency from being shifted due to the temperature.

FIG. 5 is a system block diagram of the present application example. The same components as those in
20 FIG. 1 showing the first application example are denoted by like numerals. A received signal taken in from an antenna 7 is amplified in an amplifier 8, converted to a matched signal in a SAW matched filter 18 of the present application example, multiplied in a mixer 20 by a signal
25 preceding it by one information bit and delayed in a SAW delay line 19 and thus detected, converted in a square wave output circuit 13 to a digital signal, and outputted from an output terminal 10. In the present application

example, delay detection is conducted by using an SAW element. This results in a feature that the detector circuit can be formed more simply.

FIG. 6 is a diagram showing m_j corresponding to a 25-chip code b_j of number (num) 947565 shown in TABLE 7.

FIG. 7 is a diagram showing a matched signal waveform in the case where this m_j code is used on the transmitting side and the reference code of the matched filter on the receiving side is made the same. The carrier frequency is 300 MHz, and the information rate is 1 Mbps. At this time, a favorable side lobe suppression factor (peak to side lobe ratio $D/U = 18.2$ dB) is obtained.

FIG. 8 is a diagram showing the frequency response of the matched filter of the present application example. In FIG. 8, ripples on the frequency response correspond to side lobe deterioration. For the purpose of comparison, the case where the conventional 13-chip Barker code is used will now be also described.

FIG. 9 is a diagram showing m_j corresponding to this Barker code.

FIG. 10 is a diagram showing the matched signal waveform in the case where this m_j code is used on the transmitting side and the reference code of the matched filter on the receiving side is made the same.

In the same way as the present application example, the carrier frequency was set equal to 300 MHz

and the information rate was set equal to 1 Mbps. A side lobe suppression factor (peak to side lobe ratio $D/U = 22.1$ dB) was obtained.

FIG. 11 is a diagram showing the frequency response of the matched filter in the case where the Barker code is used. It is shown that ripples are comparatively small and the side lobe suppression factor is large.

As described above, use of the present application example makes it possible to obtain a communication device having a chip length of 25 and improve significantly the processing gain at the sacrifice of only a slight side lobe deterioration as compared with the case where the conventional Barker code is used.

A fourth application example of the present invention will now be described by referring to FIGS. 12 and 13. In the above described third application example, the side lobe suppression factor was $D/U = 18.2$ dB. In the present application example, however, further side lobe suppression is conducted.

FIG. 12 is a diagram showing a reference 25-chip tap coefficient M_j of the receiving side in the present application example. In order to conduct side lobe suppression of the matched signal, respective taps are provided with weights.

FIG. 13 shows a matched signal waveform in the case where the m_j code of the third application example are used on the transmitting side and respective taps of

the matched filter of the receiving side are provided with weights corresponding to the above described reference code NJ. Coefficients of FIG. 12 were derived by using an optimization algorithm. The carrier frequency is 300 MHz, and the information rate is 1 Mbps. By doing so, a favorable side lobe suppression factor (peak to side lobe ratio $D/U = 19.8$ dB) as compared with the third application example is obtained without increasing the number of taps of the receiving side.

A fifth application example of the present invention will now be described by referring to FIGS. 14 and 15. In the fourth application example, the number of taps was set equal to 25 equally for both the transmitting side and the receiving side. In the present application example, however, the number of taps on the receiving side was set equal to 49 in order to conduct further side lobe suppression.

FIG. 14 is a diagram showing the reference 49-chip tap coefficient NJ on the receiving side of the present application example. For matched signal side lobe suppression, respective taps are provided with weights.

FIG. 15 is a diagram showing a matched signal waveform in the case where the mj code of the third application example is used on the transmitting side and respective taps of the matched filter on the receiving side are provided with weights corresponding to the above described reference code MJ. Coefficients of FIG. 14

were derived by using the optimization algorithm. The carrier frequency is 300 MHz, and the information rate is 1 Mbps. As compared with the conventional case where the Barker code is used, a favorable side lobe suppression factor (peak to side lobe ratio $D/tJ = 24.4$ dB) is obtained.

5 A sixth application example of the present invention will now be described by referring to FIG. 16. The same components as those in FIG. 5 showing the third application example are denoted by like numerals. In the third application example, demodulation is conducted directly in the transmission signal band. Since the frequency is high, however, signal
10 processing is difficult in some cases. In the present application example, the frequency is lowered by multiplying the received signal with a signal generated by an oscillator 22 conducted in a mixer 21 and thereafter demodulation processing is conducted. If the present application example is used, demodulation processing with a comparatively low frequency band is
15 possible, resulting in a feature of easy circuit design.

 A seventh application example of the present invention will now be described by referring to FIG. 17.

 FIG. 17 is a diagram showing a receiving part of a communication device in the seventh application example. The same components as those in
20 FIG. 3 showing the second application example are denoted by like numerals. In the second application example, demodulation is

conducted by using a matched filter. In the case where the information rate is slow, however, the device size of the matched filter becomes large. In the present application example, an signal outputted from a pseudo noise code generator 23 is multiplied in a mixer 24 by a carrier signal of an oscillator 25
5 having the same frequency as that of the carrier, and a resultant signal is synchronized with the received signal and it is multiplied in a mixer 26 by the received signal. As a result, a demodulated signal can be obtained. The present application example has a feature that signal demodulation can be conducted without increasing the device size even in the case where the
10 information rate is comparatively slow.

An eighth application example of the present invention will now be described by referring to FIG. 18.

FIG. 18 is a diagram showing a receiving part of a communication device in the eighth application example. The same components as those in
15 FIG. 3 showing the second application example are denoted by like numerals. In the seventh application example, a pseudo noise signal is generated to conduct demodulation. On the receiver side as well, however, a signal generator is needed, resulting in a large circuit scale. In the present application example, a carrier frequency oscillator 28 is multiplied in a mixer
20 27 by the received signal. Furthermore, a resultant signal is converted to a digital signal by a detector circuit 29 and a square wave

output circuit 30. In a digital correlation signal processing circuit 31, the digital signal is subjected to processing according to the equation of the Expression 4 and the equation of the Expression 5. In the present application example, correlation demodulation processing can be conducted by using digital
5 processing. This results in a feature that the device can be fabricated at comparatively low cost in the case where the information rate is comparatively slow, or the pseudo noise code length is short.

A ninth application example of the present invention will now be described by referring to FIG. 19.

10 FIG. 19 is a diagram showing a receiving part of a communication device in the ninth application example. The same components as those in FIG. 17 showing the seventh application example are denoted by like numerals. In the eighth application example, demodulation is conducted in the digital circuit. In the case where the information rate is fast and the pseudo
15 noise code length is long, processing cannot be conducted in some cases because the clock frequency of the digital circuit is low. In the present application example, a signal outputted from a pseudo noise code generator 23 is multiplied in a mixer 24 by a carrier signal of an oscillator 25 having the same frequency as the carrier. A resultant signal and the received signal are
20 subjected to convolution integral processing in a convolver 32 which is a correlation element. Furthermore, a resultant signal is

subjected to demodulation in a detector circuit 33. The present application example has a feature that the demodulated signal can be obtained comparatively easily so long as the carrier frequency can be synchronized with the pseudo noise code cycle even in the case where the information rate is fast and the pseudo noise code length is long.

As compared with the sixth through ninth application examples, the case where the matched filter is used as in the second and third application examples has a feature that signal synchronizing is unnecessary because the code on the receiving side is fixed. On the contrary, the sixth through ninth application examples have a feature that the reference code on the receiving side can be changed freely so as to correspond to the code on the transmitting side because the code is variable.

A tenth application example of the present invention will now be described by referring to FIG. 20.

FIG. 20 is a diagram showing a detection part of a communication device in the tenth application example. In the present application example, a delay detection system is used as the detection system, and demodulation is conducted by multiplying a current signal, in a mixer 35, by a signal preceding a current signal by one information bit supplied from a delay line 34. In the present application example, the detector circuit can be simplified.

An eleventh application example of the present invention will now be described by referring to FIG. 21.

FIG. 21 is a diagram showing a detection part of a communication device of the eleventh application example. In the present application example, a synchronous detection system is used as the detection system, and demodulation is conducted by multiplying a clock reproduced by a clock detection circuit 36, in a mixer 35, by a signal. In the present application example, a better error rate than that of the delay detection system is obtained.

A twelfth application example of the present invention will be now described by referring to FIG. 22.

FIG. 22 is a diagram showing a communication system of the twelfth application example. In the present application example, communication devices of the present system are used in a LAN. Present communication devices 41 and 42 are connected to a LAN cable 38. Present communication devices 40 and 43 are connected to terminals 39 and 44. Present communication devices 46 and 47 are connected to terminals 45 and 48. Between terminals (without a wire system between), communication can be conducted freely. If the present application example is used, it is not necessary to connect each terminal to a LAN cable, and consequently terminals can be freely moved.

INDUSTRIAL APPLICABILITY

According to the present invention, the side lobes of the correlation coefficient can be suppressed with the pseudo noise code length of at least 14 as
5 heretofore described. Therefore, the error rate can be reduced and the processing gain can be improved in a spread spectrum communication device and a communication system using the spread spectrum communication device.